

Multipor Armierungsgewebe 4x4 mm

Das Multipor Armierungsgewebe 4x4 mm ist ein alkalibeständiges Glasgittergewebe für die Innen- und Außenanwendung. Es wird mit leichtem Druck in das obere Drittel des frisch aufgezogenen Armierungsmörtels (Multipor Leichtmörtel, Multipor ExSal Therm Leichtmörtel oder Multipor Dichtschlämme) eingebettet und sollte im Stoßbereich mindestens 10 cm überlappen. Der Materialbedarf liegt bei 1,1 m²/m².

Technische Daten	Beschreibung
Produktbeschreibung	Gittergewebe aus Textilglas (E-Glas)
Eigenschaften	alkalibeständig, schiebefest, dimensionsstabil, unverrottbar
Maschenweite	4 x 4 mm
Flächengewicht	160 g/m ² ± 5%
Festigkeit - Anlieferungszustand - Nach Alterung (gemäß ETAG 004)	≥ 2.000 N/5 cm ≥ 1.000 N/5 cm (≥ 50% des Anlieferungszustandes)
Lieferformen	Rolle mit 25 m ² oder 50 m ²
Rollenabmessungen - Breite - Länge	1 m 25 oder 50 m
Materialbedarf	ca. 1,1 m ² /m ²
Gewicht	4 kg (25 m ² Rolle) 8 kg (50 m ² Rolle)
Lagerung	trocken, vor direkter Sonneneinstrahlung schützen

Xella Deutschland GmbH

Xella Kundeninformation

☎ 0800 5 235665 (freecall)

@ info@xella.com

🌐 www.multipor.de

Multipor is a registered trademark of the Xella Group.

The Multipor logo consists of the word "multipor" in a lowercase, sans-serif font. The letters "m", "p", and "r" are bolded. The text is white and is set against a solid green square background.